

Manufacturer's and Recycler recommended maintenance	Shop completed Yes/Date
Engine INSTALLATION CHECKLIST	
Replace Seals if leaking or signs of leaking	
Fill fluids to the proper levels using the proper types in accordance with the vehicle manufacturer's guidelines. Review the manufacturer's latest TECHNICAL SERVICE BULLETINS RE: Installation Guidelines and Fluid Service.	
Replace OIL FILTER	
Inspect valve cover gaskets, replace if necessary	
Replace oil pan gasket	
Clean the oil sump screen and pickup tube.	
Replace water pump.	
Replace spark plugs, if needed.	
Inspect or replace spark plug wires/coils as necessary.	
Replace thermostat.	
Replace timing belt/chain if needed.	
Flush cooling system if needed.	
Install new belts and hoses.	
Flow test radiator and replace if necessary.	

* SEE REVERSE



www.teamprp.com

1-888-577-0141 TO REORDER TAG

PART NUMBER PRP9050ENG

MANDATORY

Prior to engine start

1. Disable the ignition and fuel system to prevent the engine from starting.
2. Crank engine using the engine starter for a least 60 seconds or until the oil pressure light goes off.
3. Repeat step 2 until pressure light goes off while cranking.
4. Start engine and ensure adequate oil pressure.

Warranty is void if engine is run hot or heat tabs melted.

Warranty is void if the crankshaft is rotated in the opposite direction from which it runs.

I certify that the work has been completed per the manufacturer's and the TEAM PRP Recycler's guidelines.

Signature

Position (tech, owner, etc.)

Date

PO/Invoice Number



www.teamprp.com

© TEAM PRP 2012

WIND DIRECTION